

<b>BES. GAL-AIR 18-600</b>	<b>Specifications</b>
<b>Air Displacement</b>	<b>24.8 CFM</b>
<b>Air Delivery</b>	<b>12 CFM @ 100 PSI</b>
<b>Pressure Switch</b>	<b>Continuous run unloader valve with idle down Unload @ 125 PSI Loads @ 100 PSI</b>
<b>Engine</b>	<b>Honda GX 160 4.8 HP OHV gas engine with oil alert</b>
<b>Air tanks storage</b>	<b>3/8" x 13' copper Air cooler</b>
<b>Shipping Weight</b>	<b>70LB</b>
<b>Shipping Dimensions</b>	<b>22" x 22" x 22"</b>
<b>Fuel Capacity (Gal)</b>	<b>.95 gal.</b>
<b>Compressor Type</b>	<b>Oil-less compressor Twin opposed piston design Air cool</b>

## Features

- Lightweight 70 lbs.
- Higher CFM Delivery
- Two Year Engine Warranty
- Low Oil Shut Down
- All Steel/Aluminum Construction (No Plastic Shrouds)
- Built for Contractors in Van Nuys, California
- Rated for Continuous Use (100% Duty Cycle)
- Ball Bearing Construction Throughout
- Will start and Run in Cold Weather
- Extremely Well Balanced (no walking)
- Direct Drive Design-No Belts, Pulleys or Flywheels
- Fast, Easy, Low Cost Rebuilds

